

SERVO CABLE Li12YCV11Y



- High flexible servo cable, suitable for the use in drag-chains and in the automation area

General characteristic data

Characteristics	64-200-013	64-200-014	64-200-018	64-200-020	64-200-021
Mantle: PUR, hardly inflammable (IEC 332.1), red	X	X	X	X	
Free of halogen according to VDE 0250 Part 1					X
Low on adhesions		X			
Adhesions free	X		X	X	X
Wire identification according to VDE 47100	X	X	X	X	X
Twisted layer	X	X	X	X	
Twisted pair					X
Bend radius	7,5 x Ø (not in motion)	X	X	X	X
	15 x Ø (as drag-chain)	X	X	X	X

Article-No.	Wire-number and cross-section	Outside diameter mm	CU Weight Kg / 100 m	Weight Kg / 100 m
64-200-013	26X0,14	9,1	6,50	16,50
64-200-014	18X0,14	8,3	5,20	9,28
64-200-018	10X0,14	7,0	2,85	9,00
64-200-020	40X0,14	11,0	9,60	21,00
64-200-021	(2x2x0,25+3x2x0,14+1x2x0,5)	8,4	5,60	13,40

Environmental data

Temperature range:

Not in motion: -40 to +80°C

In motion: -5 to +80°C

