



Model Number


IMT 8-2B-NS-M3

Inductive sensor

Features

- Basic series
- increased operating distance

Connection




Safety Note



The use of this device in applications, where the safety of persons depends from the devices function, is not allowed!

Dimensions



Technical Data

General specifications

Switching element function	NPN Make function
Rated operating distance	s_n 2 mm
Installation	embeddable
Output polarity	DC
Assured operating distance	s_a 0 ... 1.62 mm
Reduction factor r_{Al}	0.45
Reduction factor r_{Cu}	0.35
Reduction factor r_{V2A}	0.7

Nominal ratings

Operating voltage	U_B 5 ... 30 V
Switching frequency	f 0 ... 3000 Hz
Reverse polarity protection	no
Short-circuit protection	yes
Voltage drop	U_d \leq 2.5 V
Operating current	I_L 0 ... 100 mA
Off-state current	I_r 0 ... 0.5 mA typ. 0.1 μ A at 25 °C
No-load supply current	I_0 \leq 15 mA
Indication of the switching state	Multihole-LED, yellow

Standard conformity

Standards	IEC / EN 60947-5-2:2004
-----------	-------------------------

Ambient conditions

Ambient temperature	-25 ... 70 °C (248 ... 343 K)
---------------------	-------------------------------

Mechanical specifications

Connection type	connector M8 x 1, 3-pin
Housing material	brass, nickel-plated
Sensing face	LCP
Protection degree	IP67

Approvals and certificates

UL approval	cULus Listed, General Purpose
-------------	-------------------------------