

# EKI-2725

## 5-port Industrial Unmanaged Gigabit Ethernet Switch

NEW



CE FCC UL

### Features

- Provides 5 Gigabit Ethernet ports with Auto MDI/MDI-X
- Supports 10/100/1000Mbps Auto Negotiation
- Supports jumbo frame transmission up to 9kbytes
- Supports 4,000 VDC Ethernet ESD protection
- Provides surge (EFT) protection 3,000 VDC for power line
- Provides Slim size, DIN-rail with IP30 metal mechanism
- Supports Redundant 12 ~ 48 VDC power input and P-Fail Relay
- Supports operating temperatures from -10 ~ 60° C
- Provides broadcast storm protection

### Introduction

The EKI-2725 comes equipped with all the standard features of the EKI family. Furthermore, it offers a +12 ~48 VDC redundant power input design, and is secured with a double protection mechanism; Power Polarity Reverse Protect and an Overload Current Reset-able Fuse. The former tolerates reverse power wiring (devices will not be damaged if the plus and minus power cables are mixed, even continuing to operate normally. The later secures the system from overload currents; when the power supply turns normal, EKI-2725 will automatically get back to work. Each port of EKI-2725 has 2 LED's to show the link status transmission speed and collision status. It also provides a relay output for an event alarm. In the event of a power failure, the built-in LED will activate the alarm to notify administrators. Engineers can simply verify the hardware status by checking the LED, and have troubleshooting easy and quick. EKI-2725 comes with compact metal housing that rates IP30 to help against from dusty industrial environments.

### Specifications

#### Communications

- **Standard** IEEE 802.3, 802.3u, 802.3x, 802.3ab
- **LAN** 10/100/1000Base-TX
- **Transmission Distance** Up to 100m (4- wire Cat.5e, Cat.6 RJ-45 cable)
- **Transmission Speed** Up to 1000 Mbps

#### Interface

- **Connectors** 5 x RJ-45  
6-pin removable screw terminal (power & relay)
- **LED Indicators** P1, P2, P-Fail  
10/100/1000TX: Link/Activity, Duplex/Collision

#### Power

- **Power Consumption** Max. 4.6W
- **Power Input** 2 x Unregulated 12 ~ 48 V<sub>DC</sub>
- **Fault Output** 1 Relay Output

#### Mechanism

- **Dimensions (W x H x D)** 37 x 140 x 95 mm
- **Enclosure** IP30, Metal shell with solid mounting kits
- **Mounting** DIN-rail, Wall

#### Protection

- **ESD (Ethernet)** 4,000 V<sub>DC</sub>
- **Surge (EFT for power)** 3,000 V<sub>DC</sub>
- **Power Reverse** Present
- **Overload** 1.8A/60V Resettable Fuse

#### Environment

- **Operating Temperature** -10 ~ 60° C (14 ~ 140° F)  
Wide Temp Model -40 ~ 75° C (-40~167° F)
- **Storage Temperature** -40~85° C (-40~185° F)
- **Operating Humidity** 5 ~ 95% (non-condensing)
- **Storage Humidity** 0 ~ 95% (non-condensing)
- **MTBF** 627,958 hrs

#### Certifications

- **Safety** UL 60950-1, CAN/CSA-C22.2 No.60950
- **EMC** U.S.A.: FCC Part 15 CISPR 22  
EU: EN55011, EN61000-6-4  
EN55022 Class A,  
EN61000-3-2/3  
EN55024  
IEC61000-4-2/3/4/5/6/8/11/12  
EN61000-6-2
- **Shock** IEC60068-2-27
- **Freefall** IEC60068-2-32
- **Vibration** IEC60068-2-6

### Ordering Information

- **EKI-2725** 5-port Industrial Unmanaged Gigabit Ethernet Switch